

# SAFETY DATA SHEET

## Klean Strip Denatured Alcohol

Page: 1

Revision: 06/11/2018  
Supersedes Revision: 12/13/2017

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Klean Strip Denatured Alcohol

**Company Name:** W. M. Barr  
2105 Channel Avenue  
Memphis, TN 38113

**Phone Number:** (901)775-0100

**Web site address:** www.wmbarr.com

**Emergency Contact:** 3E 24 Hour Emergency Contact (800)451-8346

**Information:** W.M. Barr Customer Service (800)398-3892

**Intended Use:** Cleans glass and is used as a fuel for marine stoves

**Product Code:** CSL26, GSL26, GSL26SC, QSL26, QSL26W, QSL26SC

### 2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 2

Acute Toxicity: Inhalation, Category 3

Acute Toxicity: Oral, Category 3

Acute Toxicity: Skin, Category 3

Specific Target Organ Toxicity (single exposure), Category 1



**GHS Signal Word:**

**Danger**

**GHS Hazard Phrases:**

H225: Highly flammable liquid and vapor.  
H301: Toxic if swallowed.  
H311: Toxic in contact with skin.  
H331: Toxic if inhaled.  
H370: Causes damage to organs.

**GHS Precautionary Phrases:**

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233: Keep container tightly closed.  
P240: Ground/bond container and receiving equipment.  
P241: Use explosion-proof electrical/ventilating/lighting equipment.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P260: Do not breathe gas/mist/vapors/spray.  
P264: Wash hands thoroughly after handling.  
P270: Do not eat, drink or smoke when using this product.  
P271: Use only outdoors or in a well-ventilated area.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P235: Keep cool.

**GHS Response Phrases:**

P301+310: IF SWALLOWED: Immediately P311: Call a POISON CENTER or doctor/physician.  
P302+352: IF ON SKIN: Wash with plenty of soap and water.  
P303+361+353: IF ON SKIN (or hair): P361: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P307+311: IF exposed: P311: Call a POISON CENTER or doctor/physician.  
P330: Rinse mouth.  
P363: Wash contaminated clothing before reuse.  
P370+378: In case of fire, use dry chemical powder to extinguish.

**GHS Storage and Disposal Phrases:**

P403+233: Store container tightly closed in well-ventilated place.  
P405: Store locked up.

# SAFETY DATA SHEET

## Klean Strip Denatured Alcohol

Page: 2

Revision: 06/11/2018  
Supersedes Revision: 12/13/2017

P501: Dispose of contents/container according to local, state and federal regulations.

**Emergency Overview:****OSHA Regulatory Status:** This material is classified as hazardous under OSHA regulations.**Potential Health Effects (Acute and Chronic):**  
Inhalation Acute Exposure Effects:  
Vapor harmful. May cause dizziness, headache, watering of eyes, irritation of respiratory tract, irritation to the eyes, drowsiness, nausea, other central nervous system effects, spotted or blurry vision, dilation of pupils, and convulsions.Skin Contact Acute Exposure Effects:  
May cause irritation, drying of skin, redness, and dermatitis. May cause symptoms listed under inhalation. May be absorbed through damaged skin.Eye Contact Acute Exposure Effects:  
May cause irritation.Ingestion Acute Exposure Effects:  
Poison. Cannot be made non-poisonous. May be fatal or cause blindness. May produce fluid in the lungs and pulmonary edema. May cause dizziness, headache, nausea, drowsiness, loss of coordination, stupor, reddening of face and or neck, liver, kidney and heart damage, coma, and death. May produce symptoms listed under inhalation.Chronic Exposure Effects:  
May cause symptoms listed under inhalation, dizziness, fatigue, tremors, permanent central nervous system changes, blindness, pancreatic damage, and death.Target Organs:  
Liver, kidneys, pancreas, heart, lungs, brain, central nervous system, eyes**Medical Conditions Generally Aggravated By Exposure:** Diseases of the liver, skin, lung, kidney, central nervous system, pancreas, and heart; asthma; inflammatory or fibrotic pulmonary disease; any preexisting condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease, or anemias

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
64-17-5	Ethyl alcohol {Ethanol}	30.0 -60.0 %
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	30.0 -60.0 %
108-10-1	Methyl isobutyl ketone {Hexone; Isopropylacetone; MIBK; 4-Methyl-2-pentanone}	0.1 -1.0 %

**Additional Chemical Information** Specific percentage of composition is being withheld as a trade secret.

## 4. FIRST AID MEASURES

**Emergency and First Aid Procedures:**

**Skin:**  
Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.

**Eyes:**  
Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.

**Inhalation:**  
Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

**Ingestion:**  
If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.

**Signs and Symptoms Of Exposure:**

See Potential Health Affects

**Note to Physician:**

Poison. This product contains methanol. Methanol is metabolized to formaldehyde and formic acid. These metabolites may cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used as an antidote. Methanol is effectively removed by hemodialysis. Call your local poison control center for further instructions.

## 5. FIRE FIGHTING MEASURES

**Flash Pt:** OSHA Class IB  
45.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)

**Explosive Limits:** LEL: No data. UEL: No data.

**Autoignition Pt:** No data.

**Suitable Extinguishing Media:** Use carbon dioxide, dry powder, or alcohol resistant foam.

**Unsuitable Extinguishing Media:** Water may be ineffective. Solid streams of water will likely spread the fire.

**Fire Fighting Instructions:** Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined area. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

**Flammable Properties and Hazards:** Vapors are heavier than air. Vapor may travel considerable distance to source of ignition and flash back.

**Hazardous Combustion Products:** carbon monoxide, carbon dioxide

## 6. ACCIDENTAL RELEASE MEASURES

**Steps To Be Taken In Case**

Vapors are heavier than air. Vapors may cause flash fire or ignite explosively.

**Material Is Released Or Spilled:**

Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.

Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large spills: Dike far ahead of spill for later disposal.

Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions To Be Taken in Handling:**

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms where vapors can accumulate. Vapors can accumulate and explode if ignited.

Do not use this product if the work area is not well ventilated. Use only with adequate ventilation to prevent build up of vapors.

Do not spread this product over large surface areas because fire and health safety risks will increase dramatically.

Use proper bonding and grounding when transferring material. Be aware of static electricity generation when handling material.

**Precautions To Be Taken in Storing:**

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
64-17-5	Ethyl alcohol {Ethanol}	ACGIH TLV OSHA PELs	TLV: 1000 ppm PEL: 1000 ppm	
67-56-1	Methanol {Methyl alcohol}; Carbinol; Wood alcohol}	ACGIH TLV OSHA PELs	TLV: 200 ppm STEL: 250 ppm PEL: 200 ppm	
108-10-1	Methyl isobutyl ketone {Hexone; Isopropylacetone; MIBK; 4-Methyl-2-pentanone}	ACGIH TLV	TLV: 20 ppm STEL: 75 ppm	

# SAFETY DATA SHEET

## Klean Strip Denatured Alcohol

Page: 5

Revision: 06/11/2018  
Supersedes Revision: 12/13/2017

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
108-10-1	Methyl isobutyl ketone {Hexone; Isopropylacetone; MIBK; 4-Methyl-2-pentanone} (continued)	OSHA PELs	PEL: 100 ppm	

**Respiratory Equipment (Specify Type):** For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors.

For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.

A dust mask does not provide protection against vapors.

**Eye Protection:**

Chemical splash goggles should be worn to prevent eye contact.

**Protective Gloves:**

Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile, natural rubber, and neoprene will provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.

**Other Protective Clothing:**

Various application methods can dictate the use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.

**Engineering Controls (Ventilation etc.):**

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.

**Work/Hygienic/Maintenance Practices:**

Wash hands thoroughly after use and before eating, drinking, smoking, or using the restroom.

Do not eat, drink, or smoke in the work area.

Discard any clothing or other protective equipment that cannot be decontaminated.

Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

# SAFETY DATA SHEET

## Klean Strip Denatured Alcohol

Page: 6

Revision: 06/11/2018  
Supersedes Revision: 12/13/2017

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical States:</b>	[ ] Gas	[ X ] Liquid	[ ] Solid
<b>Appearance and Odor:</b>	Water white, alcohol odor		
<b>pH:</b>	No data.		
<b>Melting Point:</b>	No data.		
<b>Boiling Point:</b>	147.00 F		
<b>Flash Pt:</b>	45.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)		
<b>Evaporation Rate:</b>	> 1		
<b>Flammability (solid, gas):</b>	No data available.		
<b>Explosive Limits:</b>	LEL: No data.		UEL: No data.
<b>Vapor Pressure (vs. Air or mm Hg):</b>	76 MM HG at 68.0 F		
<b>Vapor Density (vs. Air = 1):</b>	> 1		
<b>Specific Gravity (Water = 1):</b>	0.7934 - 0.8108		
<b>Density:</b>	6.646 LB/GL		
<b>Solubility in Water:</b>	No data.		
<b>Octanol/Water Partition Coefficient:</b>	No data.		
<b>Percent Volatile:</b>	100.0 % by weight.		
<b>VOC / Volume:</b>	793.0000 G/L		
<b>Autoignition Pt:</b>	No data.		
<b>Decomposition Temperature:</b>	No data.		
<b>Viscosity:</b>	No data.		

### 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Unstable [ ]	Stable [ X ]
<b>Conditions To Avoid - Instability:</b>	No data available.	
<b>Incompatibility - Materials To Avoid:</b>	Incompatible with strong oxidizing agents, strong acids, reactive metals, halogens, strong inorganic acids, and aldehydes.	
<b>Hazardous Decomposition or Byproducts:</b>	Decomposition may produce carbon monoxide and carbon dioxide.	
<b>Possibility of Hazardous Reactions:</b>	Will occur [ ]	Will not occur [ X ]
<b>Conditions To Avoid - Hazardous Reactions:</b>	No data available.	

## 11. TOXICOLOGICAL INFORMATION

**Toxicological Information:** This product has not been tested as a whole. Refer to section 2 for acute and chronic effects.  
 CAS# 64-17-5:  
 Acute toxicity, LD50, Oral, Rat, 7060. MG/KG.  
 Result:  
 Lungs, Thorax, or Respiration: Other changes.  
 - Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802,  
 Vol/p/yr: 16,718, 1970

CAS# 108-10-1:  
 Standard Draize Test, Eyes, Species: Rabbit, 40.00 MG, Severe.  
 Result:  
 Effects on Newborn: Growth statistics (e.g., reduced weight gain).  
 Effects on Newborn: Behavioral.  
 - Union Carbide Data Sheet, Union Carbide Corp., 39 Old Ridgebury Rd., Danbury, CT 06817,  
 Vol/p/yr: 4/25, 1958

**Carcinogenicity/Other Information:** IARC 1 - Carcinogenic to humans ACGIH  
 IARC 2B - Possibly Carcinogenic to Humans  
 A4 - Not Classifiable as a Human Carcinogen.

IARC has determined that the consumption of alcoholic beverages is casually related to the occurrence of malignant tumors of the oral cavity, pharynx, larynx, esophagus, and liver in humans. The carcinogenic response attributed to drinking alcoholic beverages has not been verified in studies with laboratory animals. Established uses of denatured ethanol and non-beverage use of pure ethanol are not considered to pose any significant cancer hazard.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
64-17-5	Ethyl alcohol {Ethanol}	n.a.	1	A4	n.a.
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	n.a.	n.a.	n.a.	n.a.
108-10-1	Methyl isobutyl ketone {Hexone; Isopropylacetone; MIBK; 4-Methyl-2-pentanone}	n.a.	2B	n.a.	n.a.

## 12. ECOLOGICAL INFORMATION

**General Ecological Information:** This product has not been tested as a whole.

## 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Dispose in accordance with applicable local, state, and federal regulations.

## 14. TRANSPORT INFORMATION

**LAND TRANSPORT (US DOT):**

**DOT Proper Shipping Name:** Alcohols, n.o.s. (Ethyl Alcohol, Methanol)  
**DOT Hazard Class:** 3 FLAMMABLE LIQUID  
**UN/NA Number:** UN1987 **Packing Group:** II



# SAFETY DATA SHEET

## Klean Strip Denatured Alcohol

Page: 8

Revision: 06/11/2018  
Supersedes Revision: 12/13/2017**Additional Transport Information:**

The shipper / supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

### 15. REGULATORY INFORMATION

**EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists**

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
64-17-5	Ethyl alcohol {Ethanol}	No	No	No
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	No	Yes 5000 LB	Yes
108-10-1	Methyl isobutyl ketone {Hexone; Isopropylacetone; MIBK; 4-Methyl-2-pentanone}	No	Yes 5000 LB	Yes

**CAS # Hazardous Components (Chemical Name)****Other US EPA or State Lists**

64-17-5	Ethyl alcohol {Ethanol}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	CAA HAP,ODC: HAP: VHAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: Yes: RDTox.
108-10-1	Methyl isobutyl ketone {Hexone; Isopropylacetone; MIBK; 4-Methyl-2-pentanone}	CAA HAP,ODC: HAP: VHAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: Yes: Canc+RDTox.

**Additional Regulatory Information**

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

### 16. OTHER INFORMATION

**Revision Date:** 06/11/2018  
**Preparer Name:** W.M. Barr EHS Dept (901)775-0100

**Additional Information About This Product:** No data available.