




MATERIAL SAFETY DATA SHEET
CRETE-LEASE 880 RELEASE AGENT

HAZARD RATING 4 = EXTREME 3 = HIGH 2 = MODERATE 1 = SLIGHT 0 = INSIGNIFICANT	 HEALTH	2
	 FIRE	2
	 REACTIVITY	0

IDENTIFICATION

PRODUCT NAME: Crete-Lease 880 Release Agent
REVISION: 1-1-06
CHEMICAL FAMILY: Hydrocarbon Mixture
CAS #: Not applicable for this mixture
MANUFACTURER TELEPHONE NUMBERS: 800-367-2020
419-669-2041
EMERGENCY TELEPHONE NUMBER: 800-424-9300 - CHEMTREC
(Transportation Emergencies)

COMPOSITIONAL INFORMATION

This section is condensed. For complete information please request our printed MSDS or e-mail us, Cresset@Cresset.com, with your name, address, etc. for quicker response.

This product poses minimal hazard to humans and the environment when used for placing concrete in a typical site or plant casting operation.

SAFETY:
These materials are non-toxic (OSHA CFR 29). OSHA, EPA and DOT define these materials as nonflammable.

ROUTE(S) OF EXPOSURE AND HEALTH EFFECTS

EYE CONTACT: Contact with the eye may cause moderate irritation.
SKIN CONTACT: Prolonged or repeated exposure may cause defatting of the skin resulting in

moderate skin irritation.

- INHALATION:** Excessive exposures may cause irritations to eyes, nose and mucous membranes. Excessive exposures may cause dizziness and other central nervous system effects.
- INGESTION:** This product has a low odor of acute toxicity. Pulmonary aspiration hazard if swallowed and vomiting occurs.
- CARCINOGENIC:** No ingredient in this product is listed as carcinogenic by IARC, NTP or OSHA.
-

FIRST AID PROCEDURES

- EYE CONTACT:** Flush with water for 15 minutes. Obtain medical assistance if irritation persists.
- SKIN CONTACT:** Wash with soap and water until no odor remains.
- INHALATION:** Move person to fresh air. If not breathing, give artificial respiration and obtain medical assistance.
- INGESTION:** Do not induce vomiting. Do not give liquids. Obtain medical assistance. Small amounts entering the mouth should be rinsed out until no taste remains.
-

PHYSICAL DATA

- FLASH POINT:** 125°F
- DENSITY:** 7.0 Pounds per Gallon
- VAPOR PRESSURE:** Less than Ether
-

FIRE FIGHTING PROCEDURES AND EXTINGUISHING MEDIA

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type of product depending on size or potential size of fire and circumstances related to the situation. Plan fire protection and response strategy through consultation with local fire

protection authorities or appropriate specialist. Self-contained breathing apparatus and full protective clothing should be worn.

REACTIVITY

REACTION WITH WATER:	Non-reactive
STABILITY:	Stable
HAZARDOUS POLYMERIZATION:	Will not occur
INCOMPATIBLE MATERIALS:	Strong oxidizing agents.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon dioxide or carbon monoxide upon thermal decomposition.

SPILL OR LEAK PROCEDURES

Prevent ignition, stop leak, ventilate area, contain spill by diking or impounding. Add sand, earth or other suitable absorbent to spill area. Wear respiratory protection for large spill, leak or release. Prevent product from entering sewers, storm drains, surface waters and soil.

DISPOSAL METHODS

Dispose of contaminated product and materials used in the cleaning of spills or leaks in a manner complying with Federal, State and Local regulations.

PROTECTION INFORMATION

EYES: Use splash proof chemical goggles or face shield when eye contact may occur.

SKIN: Use impervious gloves if prolonged or repeated skin contact cannot be avoided. Wash skin thoroughly after contact.

RESPIRATORY: Use with adequate ventilation. Ventilate as needed to comply with exposure limit. In the event of vapor concentrations exceeding the time weighted exposure limit use a NIOSH approved cartridge respirator or gas mask.

DOT and EPA (Not required for MSDS)

When transported by ground in 1 gallon bottles, 5 gallon pails, 55 gallon drums, packaged and sealed by Cresset Chemical Company, this product is not regulated by the US-DOT. When transported in 275 gallon MegaPaks, must use other US-DOT regulations. See "Ground Shipping...Cresset Products" for details.

SARA Title III Regulatory Compliance Information:

Section 312 Hazard Class: Acute, chronic, fire.

Section 313 Notification: Either none present or none present in reportable quantities.

CORPORATE STATEMENT

The information and recommendations contained herein are, to the best of Cresset Chemical Company's knowledge and belief, accurate and reliable as of the date issued. Cresset Chemical Company does not warrant or guarantee their accuracy or reliability, and shall not be liable for any loss or damage arising out of the use thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use.
