

JE HIGGINS LUMBER CO -- PLYWOODS & PARTICLE BOARDS -- 5640-00F036941

=====
Product Identification
=====

Product ID:PLYWOODS & PARTICLE BOARDS
MSDS Date:07/01/1988
FSC:5640
NIIN:00F036941
MSDS Number: BVSRY
=== Responsible Party ===
Company Name:JE HIGGINS LUMBER CO
Box:4124
City:CONCORD
State:CA
ZIP:94524-5000
Country:US
Info Phone Num:415-674-9300
Emergency Phone Num:415-674-9300
Preparer's Name:PAULINE EWART
CAGE:HIGGI

=== Contractor Identification ===

Company Name:JE HIGGINS LUMBER CO
Box:4124
City:CONCORD
State:CA
ZIP:94524-5000
Country:US
Phone:415-674-9300
CAGE:HIGGI

=====
Composition/Information on Ingredients
=====

Ingred Name:WOOD DUST
OSHA PEL:15 MG/CUM
ACGIH TLV:5 MG/CUM

Ingred Name:FORMALDEHYDE, FORMALIN (SUSPECTED HUMAN CARCINOGEN BY IARC;
ACGIH; SUSPECTED CARCINOGEN BY NTP; IARC - GROUP 2A) *94-3*
CAS:50-00-0
RTECS #:LP8925000
OSHA PEL:3 PPM
ACGIH TLV:1 PPM
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:AMMONIA, AMMONIUM HYDROXIDE-ANHYDROUS, ANHYDROUS AMMONIA
CAS:7664-41-7
RTECS #:BO0875000
Other REC Limits:25 PPM
OSHA PEL:25 PPM
ACGIH TLV:25 PPM
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:PARAFFIN WAX FUME, PARAFFIN
CAS:8002-74-2
RTECS #:RV0350000
ACGIH TLV:2 MG/CUM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INHALATION: RESPIRATORY IRRITATION.
EYES/SKIN: IRRITATION. PROLONGED EXPOSURE: DERMITITIS/RESPIRATORY

SENSITIZATION/ALLERGIC REACTIONS.

Explanation of Carcinogenicity:SEE INGREDIENTS.

Effects of Overexposure:INHALATION: RESPIRATORY IRRITATION. EYES/SKIN: IRRITATION. PROLONGED EXPOSURE: DERMITITIS/RESPIRATORY SENSITIZATION/ALLERGIC REACTIONS.

Medical Cond Aggravated by Exposure:SENSITIVE INDIVIDUALS MORE SUSCEPTIBLE TO IRRITATION.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES/SKIN: FLUSH W/WATER FOR 15 MINS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Fire Fighting Measures
=====

Extinguishing Media:WATER FOG, CO2, FOAM, DRY CHEMICAL
Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:AUTO IGNITION TEMP >400F.

=====
Handling and Storage
=====

Handling and Storage Precautions:ADEQUATE VENTILATION IN STORAGE AREAS.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPROVED FULL/HALF FACE RESPIRATOR.
Ventilation:NORMAL, LOCAL EXHAUST DURING MACHINING, GENERAL VENTILATION
Protective Gloves:REQUIRED FOR SENSATIVE INDIVIDUALS
Eye Protection:SAFETY GLASSES DURING MACHINING.
Other Protective Equipment:NOT NORMALLY NEEDED.
Work Hygienic Practices:NORMAL WORK & PERSONAL PROTECTION.
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

Appearance and Odor:WOOD FIBER SHEETS

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS, BASES, OXIDIZING AGENTS
Hazardous Decomposition Products:CO2, CO, PARTICULATE MATTER, OTHER ORGANIC COMPOUNDS.

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.